

# Environmental Declaration -Type II Self-declared Environmental Claims

**General information** 

Belimo a

Declaration type	Environmental labels and declarations - Self-declared environmental claims - Type II environmental labelling - compliant with ISO 14021:2016 This document encompasses a range of products with similar material compositions and specifically highlights the product with the greatest weight within that range.			
Owner of this declaration	BELIMO Automation AG Brunnenbachstrasse 1 8340 Hinwil Switzerland			
Description of the organisation	BELIMO Automation AG is a leading global developer, manufacturer, and distributor of field devices, which are crucial in the precise control of heating, ventilation, and air conditioning systems. Our consistent commitment to innovation, reliability, and energy efficiency directly influences system performance and efficiency.			
	Our global headquarters is in Hinwil, Switzerland, and we have a presence in more than 80 countries worldwide. Our focus on providing localised customer support and service underlines our role as a reliable international partner. Our dedication to sustainability and environmental protection is evident in our corporate strategies, daily operations, and especially in our approach to product development.			
Product-related or management system- related certifications	Quality management ISO 9001 Environmental management ISO 14001			
mo and the UN Sustainable Development Goals (SDGs)				

At Belimo, our product portfolio, business processes, and values are naturally aligned with UN Sustainable Development Goals, focusing on the environment, health and well-being, and society.

Trust, integrity, competence, and responsibility – values that lie at the foundation of environmental, economic, and social sustainability – define our corporate culture. As an employer, we support personal commitment, teamwork, cultural diversity, and the courage to take risks to inspire customers. We have designed and optimised our product portfolio to maximise energy efficiency and longevity. One hundred percent of our sales align with the UN Sustainable Development Goals.

Our overall sustainability mission is to promote global sustainability by creating healthier indoor environments that consume less energy.

**Health and well-being** Belimo products offer improved indoor air quality, promoting the health, comfort, and wellbeing of building occupants and enabling critical applications. Our intelligent HVAC components control the major factors affecting room climate and assure a stable and healthy environment (SDG 3).

**Environment** Our products save energy and reduce CO2 emissions. Moreover, they increase the energy efficiency of buildings (SDG 7) and contribute to their resilience (SDG 9), while making our cities safer and more sustainable (SDG 11). Through our activities, we contribute to doubling the global rate of improvement in energy efficiency, creating measurable sustainability benefits, and strengthening resilience and adaptive capacity to climate-related disasters (SDG 13).



### Belimo and the UN Sustainable Development Goals (SDGs)

**Society** As an employer, we continuously create excellent jobs that emphasise personal commitment, engagement, growth, teamwork, and cultural diversity (SDG 8). We uphold sustainable procurement practices and localised sourcing, minimising waste, and optimising logistics through modularising our product ranges and applying environmental management standards at our central production sites (SDG 12).

Covered products	5				
Product group:	Energy valve internal th	read fail-safe	Representative product:		EV050R2+KBAC
This document is ba covered by this dec	ased on the representative p laration.	roduct with the grea	atest weight in the produ	ict group. The list that fo	ollows includes all products
Product family:	EVR2+KBAC				
EV015R2+KBAC	EV020R2+KBAC	EV025R2+KBAC	EV032R2+KBAC	EV040R2+KBAC	EV050R2+KBAC
Product informat	ion				
	Chemical disclosure	RoHS	EU Directive 2011/65/	. ,	
			blies with the EU Directiv s materials in electrical a 1907/2006 (EC Regula	nd electronic equipmer	/hich restricts the use of nt.
			blies with the provisions on, Evaluation, Authorisa	of EC Regulation No 190	
Recycling and end	d-of-life information				
	Recycling quota 70.87 %				
		The recycling quo using the followin	ta (metal material propo g formula:	rtion) is calculated	
		Recycling quota =	100 x Metal weight / Tot	al weight	
	Recycling rate	Recycling rate 93.54 %			
		For calculating the formula is used:	e recycling rate (metal ar	nd plastic material prop	ortion), the following
		Recycling rate = 1	00 x (Metal weight + Plas	tic material weight) / To	otal weight
	Disposal	Product			
		and should not be Local and applical	to this product family s disposed of with regula de regulations apply.		osed of after their life cycle
		Packaging			
		Packaging is recyc	g providers perform the lable.	IF WORK according to RE	SY guidelines.
Environmental be	enefit				
			ored and optimised solut iency over the entire bui		stomer demands, and
		Belimo products a	-	uously optimised and e	nhanced. This is achieved by
Logistics					
	Transport		ic presence of our Custo nise transport routes.	misation Centres globa	lly, Belimo has effectively



Logistics					
		Component	Material	Weight	
	Packaging values	Folded box EV DN32-50, 580x245x145	56624-00001	392 g	

### Product materials and fire load

Ma	terial	Weight	% Weight	Fire load
Plastic ABS	5	0.97 g	<0.5%	0.03 MJ
EPD	DM	3.32 g	<0.5%	0.12 MJ
ETF	E	3.88 g	<0.5%	0.12 MJ
PA		110.42 g	2%	3.09 MJ
PC		489.11 g	8%	14.18 MJ
PET	-	0.53 g	<0.5%	0.02 MJ
PO	M	13.4 g	<0.5%	0.23 MJ
PP		0.58 g	<0.5%	0.03 MJ
PVC	2	1.94 g	<0.5%	0.03 MJ
Sili	cone	4.17 g	<0.5%	0.13 MJ
Oth	er plastic materials	315.13 g	5%	9.45 MJ
ronics Elec	ctronics	413.45 g	7%	8.27 MJ
<b>Metal</b> Alu	minium	103.01 g	2%	
Bra	SS	3576.49 g	60%	
Сор	oper	4.85 g	<0.5%	
Ste	el	463.6 g	8%	
Silio	con	93.12 g	2%	
<b>thers</b> Cer	amic	4.85 g	<0.5%	
Car	dboard	381.49 g	6%	
Total		5984.91 g		35.7 MJ

Fire load calculation according to the formula:

Fire load [MJ] = weight [kg] x energy value [MJ/kg]

#### Basic embodied carbon calculation

Calculation methodology	The embodied carbon calculation herein follows the 'Basic' methodology outlined in TM65 b the Chartered Institution of Building Services Engineers (CIBSE). This approach relies on data pertaining to the product's material composition to compute embodied carbon for both the A1 (Material Extraction) Scale-up and buffer factors are employed to account for additional li cycle stages such as A2 (Transport to Factory), A3 (Manufacturing), A4 (Transport to Site), C2 (Transport to Waste Processing), C3 (Waste Processing), and C4 (Disposal).		
Product life service			
Product complexity			
Embodied carbon results [kgCO <sub>2</sub> e]	A1: Material extraction (components that are replaced in B3)	1.62 kgCO₂e	
	A1: Material extraction (original product)	16.16 kgCO₂e	



Basic embodied carbon calculation

## A1–A4, B3, C2–C4: Total embodied carbon with scale-up and buffer factors

32.36 kgCO<sub>2</sub>e

AssumptionsA1: Material carbon coefficient sourceCIBSE TM65, Table 2.1B3: Materials replaced as part of repair (%)CIBSE TM65, Table 2.1

#### Disclaimer

This environmental declaration, classified as Type II, was prepared by Belimo Automation AG in alignment with ISO 14021 standards. This document is provided solely for informational purposes. As Belimo products continue to advance technically, we reserve the right to introduce technical modifications without prior notice or announcement.

The information in the product confirmation is based on Belimo's best knowledge at the time of release of this document. This declaration is provided on an "as is" basis without express or implied warranties or commitments of any kind.