

Insulation shell for valve R3..

- only for non-condensing applications
- easy mounting thanks to velcro strip
- can also be mounted/dismounted subsequently



Type Overview

| Type | DN | Suitable for | Weight |
|----------------|----|-------------------------|----------|
| EXT-OC-ZRN315 | 15 | R3015-.. (kvs ≤1.6) | 0.045 kg |
| EXT-OC-ZRN315G | 15 | R3015-.. (kvs ≥2.5) | 0.045 kg |
| EXT-OC-ZRN320 | 20 | R3020-.. | 0.037 kg |
| EXT-OC-ZRN325 | 25 | R3025-.. | 0.037 kg |
| EXT-OC-ZRN332 | 32 | R3032-.. | 0.038 kg |
| EXT-OC-ZRN340 | 40 | R3040-.. (kvs ≤16 / 31) | 0.045 kg |
| EXT-OC-ZRN340G | 40 | R3040-.. (kvs ≥25) | 0.045 kg |
| EXT-OC-ZRN350 | 50 | R3050-.. (kvs ≤25 / 49) | 0.058 kg |
| EXT-OC-ZRN350G | 50 | R3050-.. (kvs ≥40) | 0.058 kg |

Technical data

| | | |
|------------------------|----------------------|---|
| Functional data | Thermal conductivity | 0.035 W/mK |
| Materials | Used Materials | Polyethylen foam (PE-3015 acc. EN 12667:2001 / EN 12664:2001) |

Safety notes



- This accessory has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied during installation.
- The accessory may not be disposed of as household refuse. All locally valid regulations and requirements must be observed.